

Easy-to-use Analyzers for Rapid Lab and At-line Analysis of Moisture and Oil

OVERVIEW

The QuikCheck Analyzer is a rugged and reliable near infrared (NIR) analyzer that rapidly measures moisture and/or oil (fat) of food products. With accurate results in under 10 seconds, the QuikCheck provides rapid feedback for process control or product quality applications, improving product consistency and reducing waste.

EASY TO USE

Many products require little or no sample preparation. Simply place the sample in the dish and precise results for moisture and oil are displayed in seconds. The rotating dish averages hundreds of readings for reliable results from non-homogeneous sample types.

APPLICATIONS

General Food

- Cereal
- Coffee
- Dairy powders
- Potato processing
- Seasonings
- Corn Meal

Snack Food

- Potato chips
- Tortilla chips
- Crackers
- Cookies
- Popcorn
- Pretzels

Industrial

- Wood products
- Tobacco
- Biofuels
- Ceramics
- Fertilizers
- Detergents
- Minerals

Animal Food Products

- Hard pet food
- DDGs
- Beet pulp



QUICKCHECK FEATURES

- Obtain vital quality parameter data in seconds with little-to-no sample preparation
- Easy setup, calibration, and operation; can be delivered pre-calibrated and lab-ready
- Rugged, easy-to-clean, polycarbonate construction
- Non-destructive testing requires no hazardous chemicals
- Unaffected by relative humidity, changes in environmental or product temperature, and ambient light
- Fully modular with all components easily replaceable in the field



EASY TO CALIBRATE

The QuikCheck Analyzer is easy to calibrate and includes a simple and intuitive touchscreen interface to toggle between sample types. Units can be pre-calibrated and delivered lab-ready for many product types.

All data can be collected into a USB storage device or datalogger (via the Windows®-based ViewerSuite software add-on) for export to CSV and other useful file formats.



QuikCheck

- Rotating sample analysis
- Ideal for non-homogenous solids or powders
- Snack foods, cereals, tobacco, chemicals

ORDERING INFORMATION

| Part Number | Description |
|-------------|---|
| 466-600 | QuikCheck unit assembly for rotating sample analysis. Rugged polycarbonate housing. 6" sample bowl included. Requires 200-076A-8 Custom Filter Wheel - to be specified at the time of ordering. |

ACCESSORIES

| Part Number | Description |
|-------------|--|
| 200-076A-8 | Custom Filter Wheel – product type and constituent range to be specified at the time of ordering |
| 230-000A-S | Cal check standard (moisture only) |
| 240-000-4 | ViewerSuite software |
| 600-121A | Sample Bowl – 6" |
| 600-122A | Sample Bowl – 8" |

SPECIFICATIONS

| | |
|--|---|
| Measurement Constituents | Up to 2 components simultaneously |
| Moisture Range | Min. 0.1%, Max. 95% |
| Oil (Fat) Range | Min. 0.1%, Max 50% |
| Accuracy: (Subject to application and product type) | |
| Moisture | +/- 0.1% |
| Oils | +/- 0.2% |
| Calibration Codes | 100 |
| Physical & Operational Specifications | |
| Dimensions | 23 x 40x 47 cm L x W x H (9" x 16" x 19") |
| Weight | 9.9 kg (22 lbs) |
| Power | 90-260VAC, 50/60 Hz, 40 watts |
| Operating Temperature | 0-40°C (32-105°F) |
| Test Time | 5-10 seconds (user-definable) |
| Display | 5.7" high-resolution touch screen |

KPM Analytics

8 Technology Drive | Westborough, MA 01581 USA
Phone: +1 203.740.2999
www.kpmanalytics.com | sales@kpmanalytics.com

©Copyright 2022. All rights reserved. 04.005.0171.EN.v2

